


KI52E2

Hood, Integrated hood, Universal, Silver, 52 cm, D



TYPE

Product family: Hood • Hood Type: Integrated hood • Hood width: 52 cm • Extraction: Expulsion • EAN code: 8017709277833

AESTHETICS

Colour: Silver • Aesthetics: Universal • Design: Fully integrated • Material: Painted material

PROGRAMS / FUNCTIONS

No. of speeds: 3

CONTROLS

Control setting: Slider

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light power: 4 W • Free outlet maximum capacity: 305 m³/h • Motor power: 125 W • No. of filters: 1 • Anti-grease filters: Integrated filter • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 500 mm

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): D • Fluid Dynamic Efficiency class (FDEC): E • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): D • Annual Efficiency Consumption (AEC_{hood}): 70 kWh/year • Fluid Dynamic Efficiency (FDE): 8.1 • Lighting Efficiency (LE): 13 lux/W • Grease Filtering Efficiency (GFE): 75.1 % • Air flow at minimum speed (Q_{min}): 185 m³/h • Maximum extraction rate: 300 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 61 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 67 dB(A) • Time increase factor (F): 1.7 • Energy Efficiency Index per first cavity: 91.4 • Measured air flow rate at best efficiency point (Q_{bep}): 153 m³/h • Measured air pressure at best efficiency point (Q_{bep}): 196 Pa • Measured electric power input at best efficiency point (W_{bep}): 103 W • Normal Power of the light system (WI): 8 W • Average illumination of the light on the cooking surface (E_{middle}): 100 lux • Sound power level at highest setting (L_{wa}): 67 dB(A)

ELECTRICAL CONNECTION

Nominal power: 133 W • Voltage: 220-240 V • Frequency (Hz): 50 Hz • Power supply cable length: 1000 mm

SPEED 1

Extraction rate IEC 61591: 185 m³/h • Noise level IEC 60704-2-13: 61 dB(A) • Power: 80 W

SPEED 2

Extraction rate IEC 61591: 240 m³/h • Noise level IEC 60704-2-13: 63 dB(A) • Power: 100 W

SPEED 3

Extraction rate IEC 61591: 300 m³/h • Noise level IEC 60704-2-13: 67 dB(A) • Power: 125 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 208x522x284 • Width: 522 mm • Depth (mm): 284 mm • Product Height (mm): 208 mm

ACCESSORIES INCLUDED

Tube reduction: Yes

OPTIONAL

KITFC6191: Charcoal filter, Hoods

