

KSET56LXE2

Hood, Integrated (semi), Universal, Stainless steel, 56 cm, D



TYPE

Product family: Hood • Hood Type: Integrated (semi) • Hood width: 56 cm • Extraction: Ducted out or re-circulation possible •

EAN code: 8017709279486

AESTHETICS

Colour: Stainless steel • Finishing: Brushed • Aesthetics: Universal • Design: Visible front panel • Material: Stainless steel • Type of steel: Brushed • Glass Type: Clear

PROGRAMS / FUNCTIONS

No. of speeds: 3

CONTROLS

Control setting: Slider

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light power: 2,5 W • Light color temperature scale (°K): 3500 °K • Free outlet maximum capacity: 265 m³/h • Motor power: 115 W • No. of filters: 1 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 650 mm • Vent outlet: 120 mm • Minimum distance from ELECTRIC hob: 500 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): D • Fluid Dynamic Efficiency class (FDEC): E • Grease Filtering Efficiency Class (GFEC): D • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 68 kWh/year • Fluid Dynamic Efficiency (FDE): 8.7 • Lighting Efficiency (LE): 28.1 lux/W • Grease Filtering Efficiency (GFE): 66 % • Air flow at minimum speed (Q_{min}): 100 m³/h • Maximum extraction rate: 255 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 48 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 66 dB(A) • Time increase factor (F): 1.7 • Energy Efficiency Index per first cavity: 90.6 • Measured air flow rate at best efficiency point (Q_{bep}): 155 m³/h • Measured air pressure at best efficiency point (Q_{bep}): 210 Pa • Measured electric power input at best efficiency point (W_{bep}): 104 W • Normal Power of the light system (W_I): 5 W • Average illumination of the light on the cooking surface (E_{middle}): 141 lux • Sound power level at highest setting (L_{wa}): 66 dB(A)

ELECTRICAL CONNECTION

Nominal power: 120 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 100 m³/h • Noise level IEC 60704-2-13: 48 dB(A) • Power: 52 W

SPEED 2

Extraction rate IEC 61591: 135 m³/h • Noise level IEC 60704-2-13: 52 dB(A) • Power: 77 W

SPEED 3

Extraction rate IEC 61591: 255 m³/h • Noise level IEC 60704-2-13: 66 dB(A) • Power: 125 W

SPEED 4

INTENSIVE SPEED

LOGISTIC INFORMATION

Dimensions of the product (mm): 208x566x276 • Width: 566 mm • Depth (mm): 276 mm • Product Height (mm): 208 mm • Net weight (kg): 6.600 kg • Gross weight (kg): 7.380 kg

ACCESSORIES INCLUDED

Tube reduction: Yes

OPTIONAL

KITFC300: Charcoal filter, Hoods

